

CRYSTAL UNIT

SX-1612



Applications

- Bluetooth / Wireless LAN
- Wearable Devices
- LTE / SAS

Features

- Ultra thin / Dimensions (1.6×1.2×0.35)
- Ceramic Package
- High Reliability and High Stability
- Tight Tolerance and Stability
- Reflow Soldering / Emboss Taping



Specifications




Model	SX-1612	
Nominal frequency range	24.000~80.000 MHz	
Crystal cut	Fundamental [AT-cut]	
Storage temperature range	-40~+90°C	
Operating temperature range	-30~+85°C	-40~+105°C
Frequency temperature characteristics(Ref. to +25°C)	$\pm 15 \times 10^{-6}$	$\pm 30 \times 10^{-6}$
Frequency tolerance (at +25°C)	$\pm 10 \times 10^{-6}$	
Equivalent series resistance	100Ω : 24.000~29.999 MHz 80Ω : 30.000~53.999 MHz 60Ω : 54.000~80.000 MHz	
Load capacitance	8,10,12 pF or specify	
Shunt capacitance	3pF max.	
Level of drive	10 μW (100 μW max.)	

Package quantity: 3,000pcs max./Reel.

Outline and Dimensions [unit:mm]



Pin Connection	
#1,#3	Crystal
#2	GND
#4	GND(NC)



Land Pattern(REFERENCE)

